

TBX

MANOEUVRABLE AND MOBILE. THE TBX.



With a working length of 1000 mm, the Schechtl TBX is the smallest of our manual swivel bending machines. Its compact size makes it ideal for one-day job sites as well as for working on roofs and on scaffolding. The TBX can be installed on a workbench or in a construction vehicle. With the optional X-shaped support stand, the TBX can be quickly folded and pulled behind you like a roller suitcase.

BENEFITS

- ✓ **Practical:** Particularly small and handy
- ✓ **Flexible:** Easy installation on any workbench or in a van
- ✓ **Mobile:** Fold the machine with the X-shaped support stand and pull it behind you like a roller suitcase
- ✓ **Wear-free** and maintenance-free roller bearings
- ✓ **Reliable:** Crownable bending beam – always the right pretension for the material type and thickness

TECHNICAL DATA

Subject to change

| | | | |
|-----------------------|---|----|------|
| MODEL | TBX | | 100 |
| WORKING LENGTH | | mm | 1000 |
| OUTPUT | Steel (400N/mm ²) | mm | 0,80 |
| | Stainless steel (600N/mm ²) | mm | 0,50 |
| | Cooper (300N/mm ²) | mm | 1,00 |
| | Aluminium (250N/mm ²) | mm | 1,00 |
| | Zinc (150N/mm ²) | mm | 1,00 |
| DIMENSIONS | Length | mm | 1240 |
| | Depth | mm | 692 |
| | Overall height | mm | 1150 |
| WEIGHT | | kg | 38 |
| CLAMPING BEAMS | Opening height | mm | 45 |

SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Clamping beam rail 45° R 1 mm
-

ADD-ONS - OPTIMISE YOUR TBX

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
 - ✓ X-shaped support stand
 - ✓ Beading apparatus
-

All details onTBX