

KSV

THE ALL-PURPOSE MACHINE. THE KSV.



The Schechtl KSV is the reinforced version of the KS and also available with a working length of 2540 mm. The clamping beam consists of rolled profiles, the lower and bending beam of a steel construction. The comprehensive optional accessories and wide range of applications make the KSV the ultimate machine for the sheet metalworking trade.

BENEFITS

- ✓ **Virtually indestructible** – lasts for generations
- ✓ Realises **unusual profiles**
- ✓ **High working convenience** – back-friendly working height
- ✓ **Maintenance-free** bearings and guides
- ✓ **Versatile** through a comprehensive range of accessories

TECHNICAL DATA

Subject to change

MODEL	KSV		200	250
WORKING LENGTH		mm	2040	2540
OUTPUT	Steel (400N/mm ²)	mm	1,50	1,00
	Stainless steel (600N/mm ²)	mm	0,90	0,60
	Cooper (300N/mm ²)	mm	1,50	1,25
	Aluminium (250N/mm ²)	mm	2,00	1,50
	Zinc (150N/mm ²)	mm	3,00	2,50
DIMENSIONS	Length	mm	2675	3175
	Depth	mm	667	667
	Overall height	mm	1302	1302
WEIGHT		kg	870	1090
CLAMPING BEAMS	Opening height	mm	80	80

SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Sharp rail 20° R 1 mm offset
- ✓ Insert rail 10 mm
- ✓ Insert rail 24 mm
- ✓ Foot pedal

ADD-ONS - OPTIMISE YOUR KSV

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
- ✓ Manual back gauge 750 mm
- ✓ Beading apparatus
- ✓ Advice on rails

All details onKSV