

MBM

PRECISELY REPRODUCIBLE PROFILE QUALITY. WITH THE MBM.



Where manual swivel bending machines reach their limits, the MBM brings you a huge increase in functionality and efficiency. The MBM is ideal for thin-sheet processing of up to 1.00 mm sheet steel, for recurring single-piece production and small batch production. Even complex profiles are easily reproducible with the ECT control, which is installed as standard.

BENEFITS

- ✓ Lightweight **all-rounder** for thin-sheet processing
- ✓ **Sturdy construction** with optimally dimensioned beam elements
- ✓ **ECT control** for precisely reproducible profile quality
- ✓ **Time-saving** 1-man operation
- ✓ **High working convenience** – back-friendly working height

TECHNICAL DATA

Subject to change

| MODEL | MBM | | 250 | 310 |
|-----------------------|---|----|------|------|
| WORKING LENGTH | | mm | 2500 | 3100 |
| OUTPUT | Steel (400N/mm ²) | mm | 1,00 | 1,00 |
| | Stainless steel (600N/mm ²) | mm | 0,60 | 0,60 |
| | Cooper (300N/mm ²) | mm | 1,00 | 1,00 |
| | Aluminium (250N/mm ²) | mm | 1,50 | 1,50 |
| | Zinc (150N/mm ²) | mm | 2,00 | 2,00 |
| DIMENSIONS | Length | mm | 3325 | 3825 |
| | Depth | mm | 1690 | 1690 |
| | Overall height | mm | 1645 | 1645 |
| WEIGHT | | kg | 1700 | 1860 |
| CLAMPING BEAMS | Opening height | mm | 130 | 130 |

CONTROLS

The MBM is available with the following controls.

- ✓ ECT
-

SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Sharp rail 20° R 1 mm offset
 - ✓ Insert rail 10 mm
 - ✓ Insert rail 24 mm
 - ✓ Motorized backgauge 6-750 mm
 - ✓ Foot switch
-

ADD-ONS - OPTIMISE YOUR MBM

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear RSL
 - ✓ Conical backgauge fingers
 - ✓ Advice on rails
-

All details on MBM