

# SB

YOUR SHINGLE SPECIALIST. THE SB.



The Schechtl SB produces shingles quickly and simply. To do this, the SB bends two edges or hems which are arranged at an angle of 90 degrees to each other. The clamping beams are equipped with replaceable segments, making the production of square and rectangular shingles or other components extremely easy. In addition, with the SB, the usual 24 work steps are reduced to 8. This is a time-saving of approx. 70%.

## BENEFITS

- ✓ **Repeat accuracy:** 2 precision 180° edge bends in one work step
- ✓ **Cost-efficient:** 70 % time saving during shingle bending
- ✓ **Convenience:** 24 conventional work steps are reduced to 8
- ✓ **Easy movement** on 4 castors
- ✓ **1-man operation**

## TECHNICAL DATA

Subject to change

|                       |   |    |      |
|-----------------------|---|----|------|
| <b>MODEL</b>          | <b>SB</b>                               |    | 50   |
| <b>WORKING LENGTH</b> |   | mm | 550  |
| <b>OUTPUT</b>         | Steel (400N/mm <sup>2</sup> )           | mm | 1,00 |
|                       | Stainless steel (600N/mm <sup>2</sup> ) | mm | 0,60 |
|                       | Cooper (300N/mm <sup>2</sup> )          | mm | 1,25 |
|                       | Aluminium (250N/mm <sup>2</sup> )       | mm | 1,50 |
|                       | Zinc (150N/mm <sup>2</sup> )            | mm | 1,50 |
| <b>DIMENSIONS</b>     | Length                                  | mm | 1410 |
|                       | Depth                                   | mm | 1005 |
|                       | Overall height                          | mm | 1600 |
| <b>WEIGHT</b>         |   | kg | 265  |
| <b>CLAMPING BEAMS</b> | Opening height                          | mm | 86   |

# SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Segments with quick clamping system
- ✓ Storage box
- ✓ Backgauge
- ✓ Castors

---

All details onSB