

# TBS

MANOEUVRABLE AND MOBILE. THE TBS.



The Schechtl TBS is the smallest in our range of manual segment swivel bending machines, but a giant when it comes to flexibility on the job site. Its compact dimensions allow you to move the TBS around easily on the job site – between floors, on scaffolding and in small areas. Moreover, the TBS can be installed on a workbench or in a construction vehicle.

## BENEFITS

- ✓ Bending **boxes, cassettes & co.** on the job site
- ✓ **Rational and productive** – all segments are adjusted without the use of tools
- ✓ **Without effort:** 1 man working alone can transport the TBS quite easily
- ✓ **Flexible:** Easy installation on any workbench or in a van
- ✓ **Safe storage** of the segments in a separate case

## TECHNICAL DATA

Subject to change

MODEL	TBS		125	100
<b>WORKING LENGTH</b>		mm	1250	1000
<b>OUTPUT</b>	Steel (400N/mm <sup>2</sup> )	mm	0,63	0,63
	Stainless steel (600N/mm <sup>2</sup> )	mm	0,50	0,50
	Cooper (300N/mm <sup>2</sup> )	mm	0,80	0,80
	Aluminium (250N/mm <sup>2</sup> )	mm	1,00	1,00
	Zinc (150N/mm <sup>2</sup> )	mm	1,00	1,00
<b>DIMENSIONS</b>	Length	mm	1369	1235
	Depth	mm	698	698
	Overall height	mm	1156	1133
<b>WEIGHT</b>		kg	114	84
<b>CLAMPING BEAMS</b>	Opening height	mm	45	45

# SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Segments with quick clamping system
  - ✓ Segment box
- 

# ADD-ONS - OPTIMISE YOUR TBS

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
  - ✓ X-shaped support stand
  - ✓ Stand bases
- 

All details onTBS