

With a working length of 1000 mm, the Schechtl TBX is the smallest of our manual swivel bending machines. Its compact size makes it ideal for one-day job sites as well as for working on roofs and on scaffolding. The TBX can be installed on a workbench or in a construction vehicle. With the optional X-shaped support stand, the TBX can be quickly folded and pulled behind you like a roller suitcase.

BENEFITS

- ✓ Practical: Particularly small and handy
- ✓ Flexible: Easy installation on any workbench or in a van
- ✓ **Mobile:** Fold the machine with the X-shaped support stand and pull it behind you like a roller suitcase
- ✓ Wear-free and maintenance-free roller bearings
- ✓ Reliable: Crownable bending beam always the right pretension for the material type and thickness

TECHNICAL DATA

Subject to change

MODEL	TBX		100
WORKING LENGTH		mm	1000
OUTPUT	Steel (400N/mm²)	mm	0,80
	Stainless steel (600N/m	r mm	0,50
	Cooper (300N/mm²)	mm	1,00
	Aluminium (250N/mm²)	mm	1,00
	Zinc (150N/mm²)	mm	1,00
DIMENSIONS	Length	mm	1240
	Depth	mm	692
	Overall height	mm	1150
WEIGHT		kg	38
CLAMPING BEAMS	Opening height	mm	45

SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

✓ Clamping beam rail 45° R 1 mm

ADD-ONS - OPTIMISE YOUR TBX

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
- ✓ X-shaped support stand
- Beading apparatus

All details onTBX